



# Νέο DOBLO



## Βασικός Εξοπλισμός

Μηχανικό Κιβώτιο ταχυτήτων (5speed 1,3- 6speed 1,6)  
ESC (Electronic Stability Control)  
ABS / VDC (Vehicle Dynamic Control)  
**Αερόσακος οδηγού / συνοδηγού**  
Σύστημα Κλιματισμού  
Κεντρικό σύστημα Κλειδώματος με τηλεχειριστήριο  
Ηλεκτρικά παράθυρα  
Υδραυλικό Τιμόνι  
Trip Computer/Στροφόμετρο/Εξωτερική θερμοκρασία  
Αντιστρεπτική δοκός  
**Πισινή διπλή πόρτα με τζάμια (θερμαινόμενα)**  
Ηλεκτρικοί – θερμαινόμενοι εξωτερικοί καθρέπτες  
**Πλευρικές συρόμενες πόρτες και από τις δύο πλευρές**  
Ρυθμιζόμενο κάθισμα οδηγού ως προς το ύψος  
Κάθισμα οδηγού με στήριξη μέσης  
Ρυθμιζόμενο Τιμόνι καθ' ύψος  
Φώτα Ομίχλης μπροστά (μόνο στο Maxi)  
Διαχωριστικό καμπίνας – χώρου φόρτωσης με τζάμι  
Ράδιο USB/AUX, Bluetooth  
Αντικλεπτικό σύστημα (Fiat code Immobilizer)  
Δοκοί ασφαλείας στις πόρτες  
Σύστημα πρόληψης φωτιάς (FPS)  
Επένδυση χώρου φόρτωσης (PVC)  
Εφεδρικός τροχός κανονικών διαστάσεων  
Τασάκι – αναπτήρας  
Start/Stop Eco Pack




## Προαιρετικός Εξοπλισμός

Υποβοήθηση Παρκαρίσματος (parking sensors)	€235
Cruise Control	€295


Model Code	Type	Volume m <sup>3</sup>	Payload kg	cc	bhp	Consumption (L/100Km - Ø)	Price OTR (€)
263.11W.2	1,3 Multijet <sub>2</sub> L1H1	3,4	750	1248	95	5,1 – 5,7	17,200
263.2BW.2	1,3 Multijet <sub>2</sub> Maxi L2H1	4,2	900	1248	95	5,1 – 5,7	17,500
263.2BY.2	1,6 Multijet <sub>2</sub> Maxi L2H1	4,2	900	1598	105	5,2 – 5,7	18,200
263.21Z.2	1,6 Multijet <sub>2</sub> Maxi L2H1	4,2	900	1598	120	5,2 – 5,7	18,500
263.H1Y.2	1.6 Multijet <sub>2</sub> Maxi XL L2H2	5.0	1000	1598	105	5,2 – 5,7	19,300

ΟΙ ΠΙΟ ΠΑΝΩ ΤΙΜΕΣ ΠΕΡΙΛΑΜΒΑΝΟΥΝ 19% Φ.Π.Α., ΤΕΛΗ ΕΓΓΡΑΦΗΣ ΚΑΙ ΑΔΕΙΑ ΚΥΚΛΟΦΟΡΙΑΣ  
ΤΙΜΕΣ ΚΑΙ ΕΞΟΠΛΙΣΜΟΣ ΥΠΟΚΕΙΝΤΑΙ ΣΕ ΑΛΛΑΓΕΣ ΧΩΡΙΣ ΠΡΟΕΙΔΟΠΟΙΗΣΗ . Οι τιμές ισχύουν από 01/12/2019


## Εξωτερικές Διαστάσεις Fiat Doblo Van 3,4m<sup>3</sup>



## Fiat Doblo Maxi Van 4,2m<sup>3</sup>



## Fiat Doblo XL Van 5m<sup>3</sup>



## Εσωτερικές Διαστάσεις (Χώρος φόρτωσης)

External Dimensions (mm)	Standard Wheelbase	Maxi	XL
Loading capacity (m <sup>3</sup> )	3,4	4,2	5,0
Wheelbase	2755	3105	3105
Length	4406	4756	4756
Width	1832	1832	1832
Front Track	1510	1510	1510
Rear Track	1530	1530	1530
Max height (unladen)	1845	1880	2125
Front Protection	911	911	911
Rear Protection	740	740	740

Rear Door (mm)	STD	Maxi	XL
Width	1231	1231	1231
Height	1250	1250	1455
Rear Door (mm)			
Width	1231	1231	1231
Height	1250	1250	1455
Sliding side door (mm)			
Width	700	700	700
Height	1175	1175	1175
Load compartment (mm)			
Length	1820	2170	2170
Width	1714	1714	1714
Height	1305	1305	1550
Width between wheel arches	1230	1230	1230
Load threshold height (unladen)	545	545	545
Loading Capacity including driver (kg)	750	900	1005

## Επιλογή Κινητήρα:

### 1.3 MultiJet<sub>2</sub> 95 HP Euro 6d

**Displacement:** 1,248 cm<sup>3</sup>  
**Power:** 95 HP  
**Max torque:** 200 Nm at 1500 rpm  
**Common Rail MultiJet<sub>2</sub> direct injection electronically controlled, turbo and intercooler**  
 - With DPF particulate filter  
 - ECOJet Pack with Start&Stop  
**Top speed:** 161 km/h  
**Combined consumption (l/100 km):** 5.1 - 5.7  
**CO2 emissions (g/km):** 134 - 150  
**Emissions level:**  
 E6D-temp ECOJET with DPF, S&S and  
 ECOPack  
**Gearbox: number of gears:** 5 + R  
**Timing system:** 2 OHC (with chain) with hydraulic  
 tappets 4 valves per cylinder

### 1.6 MultiJet<sub>2</sub> 105-120 HP Euro 6d

**Displacement:** 1.598 cm<sup>3</sup>  
**Power:** 105-120 HP  
**Max torque:** 320 Nm at 1750 rpm  
**Common Rail MultiJet<sub>2</sub> direct injection electronically controlled, turbo and intercooler**  
 - With DPF particulate filter  
 - ECOJet Pack with Start&Stop  
**Top speed:** 176 km/h  
**Combined consumption (l/100 km):** 5.2 - 5.7  
**CO2 emissions (g/km):** 139 - 152  
**Emissions level:** E6D-temp ECOJET with DPF, S&S and  
 ECOPack  
**Gearbox: number of gears:** 6 + R  
**Timing system:** 2 OHC (tooth belt) with hydraulic tappets  
 4 valves per cylinder

## Συντήρηση

Προγραμματισμένο σέρβις κάθε 30,000 χλμ ή μία φορά τον χρόνο (αλλαγή λαδιού κάθε 10.000χλμ)

**5 χρόνια εργοστασιακή εγγύηση για ολόκληρο το όχημα ή 150,000 χλμ., όποιο εκ των δύο επέλθει πρώτο – Bumper to Bumper**



Technical Specification			
Diesel	95 MULTIJET <sub>2</sub>	105 MULTIJET <sub>2</sub>	120 MULTIJET <sub>2</sub>
<b>Engine</b>			
No. of cylinders, layout	4 in-line, transverse front	4 in-line, transverse front	4 in-line, transverse front
Displacement (cm <sup>3</sup> )	1248	1598	1598
Emissions level	Euro 6D-temp with DPF and Start&Stop (ECOJET)	Euro 6D-temp with DPF and Start&Stop (ECOJET)	Euro 6d-TEMP with DPF and Start&Stop (ECOJET)
Compression ratio	16.8:1	16.5:1	16.5:1
EC Max power: kW (HP) at rpm	70 (95) 3750	77 (105) 3750	88 (120) 3750
EC Max torque: Nm @ rpm	200 (20.4) 1500	320 (30.6) 1750	320 (32.6) 1750
Timing system (control)	2 OHC (with chain) with hydraulic tappets 4 valves per cylinder	2 OHC (toothed belt) with hydraulic tappets 4 valves per cylinder	2 OHC (toothed belt) with hydraulic tappets 4 valves per cylinder
Fuel included	diesel fuel for motor vehicles (EN 590)	diesel fuel for motor vehicles (EN 590)	diesel fuel for motor vehicles (EN 590)
Supply	Common Rail MultiJet, direct injection electronically controlled, turbo and intercooler	Common Rail MultiJet, direct injection electronically controlled, turbo and intercooler	Common Rail MultiJet, direct injection electronically controlled, turbo and intercooler
Ignition	by compression	by compression	by compression
<b>Transmission</b>			
Drive	front	front	front
Clutch	dry, single plate with cup engagement spring and hydraulic operation	dry, single plate with cup engagement spring and hydraulic operation	dry, single plate with cup engagement spring and hydraulic operation
Gearbox: number of gears	5 + R	6 + R	6 + R
<b>Steering</b>			
Type	rack and pinion with hydraulic power steering	rack and pinion with hydraulic power steering	rack and pinion with hydraulic power steering
Turning circle (kerb-to-kerb)	11.2/12.5 (Max)	11.2/12.5 (Max and XL)	11.2 / 12.5 (Long Wheelbase)
<b>Braking system - D (self-ventilated disc) - T (drum)</b>			
Type	hydraulic system with 2 crossover independent circuits	hydraulic system with 2 crossover independent circuits	hydraulic system with 2 crossover independent circuits
Front: ø mm	D 284 - D 305 (Maxi and extra capacity)	D284 / D305 (Maxi and extra capacity)	D284 / D305 (Maxi and 120 HP)
Rear: ø mm	T 228 - T 254 (Maxi and extra capacity and Comb)	T 228 - T 254 (Maxi and extra capacity and Comb)	T 254
Servo brake: ø	10"	10"	10"
<b>Suspension</b>			
Front	independent, MacPherson type with wishbones secured to an auxiliary crossmember, telescopic hydraulic shock absorbers, coil springs and anti-roll bar	independent, MacPherson type with wishbones secured to an auxiliary crossmember, telescopic hydraulic shock absorbers, coil springs and anti-roll bar	independent, MacPherson type with wishbones secured to an auxiliary crossmember, telescopic hydraulic shock absorbers, coil springs and anti-roll bar
Rear	Bi-link independent, coil springs, telescopic shock absorbers with dual calibration and anti-roll bar (according to versions)	Bi-link independent, coil springs, telescopic shock absorbers with dual calibration and anti-roll bar (according to versions)	Bi-link independent, coil springs, telescopic shock absorbers with dual calibration and anti-roll bar (according to versions)
<b>Wheels</b>			
Tyres	185/65 R 15 - 195/60 R 16	195/65 R 15 - 195/60 R 16	195/60 R 16
<b>Electrical system (12V)</b>			
Battery capacity (Ah)	63	50 / 60 / 63	72
Alternator current (A)	150	150	150 / 180
<b>Refuelling</b>			
Fuel tank capacity (litres)	60	60	60
Urea tank Capacity (Litres)	14	14	14 / 13*
<b>Performance and fuel consumption - Cargo SWB</b>	<b>EBD-temp ECOJET with DPF, S&amp;S and ECOPack</b>	<b>EBD-temp ECOJET with DPF, S&amp;S and ECOPack</b>	<b>EBD-temp ECOJET with DPF, S&amp;S and ECOPack</b>
Top speed (km/h)	161	170	176
Combined consumption (l/100 km)	5.1-5.7 <sup>(B)</sup>	5.2-5.7 <sup>(B)</sup>	5.2-5.7 <sup>(B)</sup>
CO <sub>2</sub> emissions (g/km)	134-150 <sup>(B)</sup>	139-152 <sup>(B)</sup>	139-152 <sup>(B)</sup>
All values are referred to NI homologation			
* Urea Tank for work up 13 Lt			